



A superior synthetic heat transfer fluid that delivers outstanding performance and thermal stability at high temperatures.

1. PRODUCT AND COMPANY IDENTIFICATION

Product name

Globaltherm® Omnitech
Heat transfer fluid

Company Information

Globaltherm, Cold Meece
Estate, Cold Meece, Stone,
Stafford, ST15 0SP, UK

Emergency telephone

+44 (0) 1785 760555

Web

www.globaltherm.org

2. PRODUCT DESCRIPTION

A superior synthetic heat transfer fluid that delivers outstanding performance and thermal stability at continuously high operating temperatures.

With low vapour pressure, high thermal conductivity, and oxidation stability,

[Globaltherm® Omnitech](#)

Heat transfer fluid offers excellent heat transfer properties over extended periods operating at temperatures up to 400°C.

Maximum heat transmission to the process vessel or equipment will allow the use of smaller circulating system pumps, valves, and heating coils.

Used fluid may be disposed of through several environmentally acceptable methods, such as used oil recycling or heavy fuels burning. Talk to us about our all-inclusive used oil reprocessing services.

NOTE: When draining hot fluid after flushing, normal safety precautions should be taken to prevent burns and the risk of fire.

3. APPLICATIONS

[Globaltherm® Omnitech](#) Heat transfer fluid is recommended for use in non-pressurized, indirectly heated, closed loop, liquid phase heat transfer systems operating at bulk fluid temperatures up to 400°C.



Globaltherm® Omnitech Heat transfer fluid is recommended for heat transfer systems operating under mild temperature conditions, where a good low temperature fluidity is required to ensure the correct flow rate during start-up.

4. SERVICE CONSIDERATIONS

As with any heat transfer oil, certain precautions should be taken to ensure satisfactory performance of Globaltherm® Omnitech Heat transfer fluid in service. These include:

- Before full temperature is imposed, all air and water should be completely vented.
- Hot oil is rapidly oxidised by air, causing thickening and deposit formation. At places where the oil is in contact with the atmosphere, e.g. the expansion vessel, the oil should not exceed 70°C for prolonged times or the oil needs to be blanketed with inert gas. Copper and its alloys promote rapid oil degradation in the presence of air and need to be avoided at these places.
- Hot oil circulating pumps must be checked frequently to prevent air from entering. Always use fresh fluid to top off system. Fluid burped out the vent or collected in drip pans should be discarded.

An analytical routine check of the heat transfer medium, while it is hot and circulating, should be part of the routine maintenance plan. This check should be carried out at least once a year, preferably three to four times a year. Testing can be carried out by Global Heat Transfer - via the Thermocare® lifecycle management programme - to all users of Globaltherm® Heat transfer fluids. The thermal fluid parameters which are measured will allow our experts an accurate assessment of the condition of the fluid. This way, Thermocare® testing and analysis programmes ensure prolonged and trouble-free operation of the fluid. Changes to the condition of the fluid are quickly detected and managed with Thermocare® and can be avoided in time before more extensive damage (to both system and fluid) and further costs are incurred.

Phone: +44 (0) 1785 760555; fax: +44 (0) 1785 760444 to ask about Thermocare® preventative maintenance programmes and heat transfer fluid testing and analysis.

5. COMPATIBILITY

While unused Globaltherm® Omnitech Heat transfer fluid is compatible with most organic and synthetic heat transfer oils prior laboratory testing is recommended before topping-up the system with this product. Adding Globaltherm® Omnitech Heat transfer fluid as a top-up to used fluids may help to increase fluid life (i.e., aromatic types). Please contact the technical team for more information about lab services and sample and analysis on +44 (0) 1785 760555.

6. HEALTH AND SAFETY

Globaltherm® Omnitech Heat transfer fluid presents no hazard to health or safety under good standards of industrial and personal hygiene. Full details of health and medical procedures are contained in the Material Safety Data Sheet. Please contact the technical team on +44 (0) 1785 760555 for more information.

7. PHYSICAL AND CHEMICAL PROPERTIES

Parameter	Unit	Code (ASTM/ISO/DIN)	Result
Appearance	N/A	N/A	Clear-to-light yellow liquid with a geranium-like odour
Operating Range	°C (°F)	N/A	15 to 400 (59 to 752)
Density @ 25°C	kg/m ³	ASTM D4052	1056
Kin. Viscosity 40°C	mm ² /s (cSt)	ASTM D445	2.5
Kin. Viscosity 100°C	mm ² /s (cSt)	ASTM D445	0.97
Flash Point PMC	°C	ASTM D93	113
Flash Point COC	°C	ASTM D92	123
Coefficient of thermal expansion	°C		0.000979/°C
Autoignition Point	°C	ASTM E659	621
Pour Point	°C	ISO 3016	11
Neutralisation Nr (acid), TAN	mgKOH/g	ASTM D974	<0.2
Maximum Bulk Temperature	°C	NTR	400
Maximum Film Temperature	°C	NTR	425
Boiling Point at 1013 mbar	°C	NTR	257
Average Molecular Weight	NTR	NTR	166
Moisture Content	PPM	ASTM D6304	<300

Note: The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved. This edition supersedes all previous editions and information contained within them. Typical values should not be construed as a guaranteed analysis of any specific lot or as specifications for the product. Abbreviations: OC, open cup test; COC, Cleveland open cup test; and, NTR, no test reported.

8. OTHER INFORMATION

PI Creation Date 18th May 2012 (#3) Revision date 5th July 2013 (#4)



THERMOCARE® IS THE AWARD WINNING
24/7 REAL-TIME CONDITION MONITORING AND
MANAGEMENT SYSTEM FOR HEAT TRANSFER FLUID



thermocare®

**PREVENTATIVE MAINTENANCE FOR COST,
RISK AND PERFORMANCE OPTIMISATION**

Thermocare® will also extend the life of your thermal fluid and reduce your environmental impact.

It's all you need to stay safe, reduce costs and improve productivity for a straightforward fixed cost.

And, what's more we have over 25 years' experience in thermal fluid management so you couldn't be in better hands.

GET IN TOUCH

GLOBALTHERM®, Cold Meece Estate, Cold Meece, Stone, Stafford, ST15 OSP, UK

Call +44 (0) 1785 760555 **Freephone UK** 0800 298 0488

Email enquiries@globaltherm.org **Find out more** www.globaltherm.org

